



Specialty Oil Company, Inc.

Material Safety Data Sheet

Trade Name and Synonyms Partner 40:1	
Manufacturer's Name WESTLAND OIL COMPANY	Emergency Telephone No. (318) 688-1300
Address P. O. Box 8098, Shreveport, Louisiana 71148	
Chemical Name and/or Family or Description Two-Cycle Engine Oil	
THIS PRODUCT IS CLASSIFIED AS: <input checked="" type="checkbox"/> NOT HAZARDOUS <input type="checkbox"/> HAZARDOUS BY DEFINITION NO. (S) _____ ON ATTACHED EXPLANATION SHEET	

warning statement

NONE CONSIDERED NECESSARY

Occupational Control Procedures

Protective equipment (Type)

- Eyes: Chemical type goggles or face shield optional
- Skin: Exposed employees should exercise reasonable personal cleanliness; this includes cleansing exposed skin areas several times daily with soap and water and laundering or dry cleaning soiled work clothing at least weekly.
- Inhalation: None required if exposures are within permissible concentrations; see below.
- Ventilation Required: Normal

Permissible Concentrations:

Air: 5 mg/cubic meter of air for mineral oil mist averaged over an 8 hour daily exposure, (ACGIH, 1982).

Emergency & First Aid Procedures

First Aid

- Eyes: As with most foreign materials, should eye contact occur, flush eyes with plenty of water.
- Skin: Wash exposed areas with soap and water
- Ingestion: Do not induce vomiting. Call a physician.
- Inhalation: Remove from contaminated area.
- Other instructions: None.



Specialty Oil Company, Inc.

Physiological Effects

Effects of Exposure

Acute:

Eyes: N.D. Believed to be minimally irritating.

Skin: N.D. Believed to be minimally irritating.

Respiratory System: N.D. Believed to be minimally irritating if not in excess of permissible concentrations; see page 1.

Chronic: N.D.

Other:

Sensitization Properties:

Skin: Yes No Unknown

Respiratory: Yes No Unknown

Median Lethal Dose (LD₅₀LC₅₀) (Species)

Oral N.O.: Practically non-toxic

Inhalation N.D.

Dermal N.D.; practically non-toxic

Other N.D.

Irritation Index. Estimation of Irritation (Species)

Skin N.D.; no appreciable effect.

Eyes N.D.; no appreciable effect.

Symptoms of Exposure N.D.; none expected except possible minimal irritation

Fire Protection Information

Ignition Temp. F. N.D. Flash Point F. (Method) 480F (COC)

Flammable Limits % Lower N.D. Upper N.D.

Products Evolved When Subjected to Heat or Combustion:

Carbon monoxide, carbon dioxide, aldehydes and ketones, combustion products of nitrogen and sulfur.

Recommended Fire Extinguishing Agents And Special Procedures:

According to the National Fire Protection Association Guide, use water spray, dry chemical, foam, or carbon dioxide. Water or foam may cause frothing. Use water to cool fire-exposed containers. If a leak or spill has not ignited, use water spray to disperse the vapors and to provide protection for persons attempting to stop the leak.

Unusual or Explosive Hazards:

None

N.D. - Not Determined
 < Less Than

N.A. - Not Applicable
 > Greater Than



Specialty Oil Company, Inc.

Composition

Components Presenting a Significant Hazard	%
None	
Other Components	%
Mineral Oil	95 - 100
Additive Package	1 - 5
Automate Blue #8 Dye	Less than 1

Additional Comments

To determine applicability or effect of any law or regulation with respect to this product, user should consult his legal advisor or the appropriate agency. Specialty Oil does not undertake to furnish advice on such matters.

By L: Hicks Title Quality Control Manager
 Date: 11-25-85 ~~XXX~~ Revised ~~XXXXXXXXXX~~

N.D. - Not Determined
 < Less Than

N.A. - Not Applicable
 > Greater Than