

**MATERIAL SAFETY DATA SHEET**  
Required under USDL Safety and Health Regulations

**SECTION I - CHEMICAL COMPANY AND PRODUCT IDENTIFICATION**

**POWER SERVICE PRODUCTS**  
**P.O. BOX 1089**  
**WEATHERFORD, TEXAS 76086**  
**817/599-9486**

PS 1025, 1041, 1155  
32oz 96oz 55 gal.

**Product Name:** DIESEL FUEL SUPPLEMENT  
**Synonyms:** DIESEL FUEL ADDITIVE  
**Generic/Chemical Name:** HYDROCARBONS, HYDROXY COMPOUNDS  
**MSDS Preparation Date:** July 24, 1998 - supersedes May 27, 1997  
**Emergency Phone Number:** 800/424-9300

**SECTION II - COMPOSITION/INFORMATION OF INGREDIENTS**

<u>INGREDIENT</u>	<u>PERCENT</u>
HYDROCARBONS	1 - 3
HYDROXY COMPOUNDS	70 - 80
AROMATICS	20 - 30

This product is a proprietary complex mixture of petroleum Hydrocarbons and Hydroxy Compounds. Specific chemical information is being withheld as a Trade Secret. Specific chemical information will be made available to health professionals in accordance with 29 CFR 1910.1200.

**SECTION III - HAZARD IDENTIFICATION**

**EMERGENCY AND FIRST AID PROCEDURES:** If overcome by vapors, remove from exposure immediately call a physician. If breathing is irregular or stopped, start resuscitation, administer oxygen. If swallowed, do not induce vomiting; call a physician. Remove contaminated clothing and wash skin with soap and water. Flush eyes with water until irritation subsides.

**PRIMARY ROUTE (S) OF ENTRY:** INGESTION AND INHALATION

**VARIABILITY AMONG INDIVIDUALS:** Health Studies have shown that many petroleum hydrocarbons and synthetic lubricants pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists and fumes should be minimized.

**NATURE OF HAZARD AND TOXICITY INFORMATION:** Prolonged or repeated skin contact with this product tends to remove skin oils possibly leading to irritation and dermatitis; however, based on human experiences and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant".

Potential risk to humans can be minimized by observing good work practices and personal hygiene procedures generally recommended for petroleum products. The product has a low order of acute toxicity, but minute amounts aspirated into the lungs during ingestion may cause severe pulmonary injury or death.

**SECTION IV - FIRST AID MEASURES**

**EYE CONTACT:** Flush eyes with large amounts of water until irritation subsides. If irritation persists, get medical attention.

**SKIN CONTACT:** Flush with large amounts of water, use soap if available. Remove grossly contaminated clothing, including shoes and laundry before reuse.

**INHALATION:** Using proper respiration protection. Immediately remove the affected victim from exposure. Administer artificial respiration if breathing is stopped. Keep at rest. Call for prompt medical attention.

**INGESTION:** If swallowed do not induce vomiting. Keep at rest. Get prompt medical attention.

**SECTION V - FIRE AND EXPLOSION HAZARD DATA**

**FLASH POINT:** ..... 53°F (TCC)

**FLAMMABLE LIMITS:** lower ..... 2 upper ..... 12

**EXTINGUISHING MEDIA:** Alcohol resistant foam, dry chemical, CO<sub>2</sub>, waterspray or fog.

**SPECIAL FIRE FIGHTING PROCEDURES:** Use air-supplied rescue equipment for enclosed areas. Cool exposed containers with water.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Do not store or mix with strong oxidants or combustible liquids.

**EMPTY CONTAINERS CONTAIN FLAMMABLE VAPORS: "DO NOT USE CUTTING TORCH EQUIPMENT OR ANY OTHER FLAME ON ANY EMPTY CONTAINER".**

**SECTION VI - ACCIDENTAL RELEASE PROCEDURES**

**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:** Remove all ignition sources. Keep people away. Recover free liquid. Add absorbent to spill area. Avoid breathing vapors. Ventilate enclosed spaces. Open all windows and doors. Keep petroleum products out of public sewers, streams and waterways.

**SECTION VII - HANDLING AND STORAGE**

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:** Keep containers closed. Keep away from heat, sparks and open flames.

**CONTAINERS ARE STRICTLY "SINGLE TRIP CONTAINERS." THEY ARE NOT TO BE USED FOR ANY REASON AFTER BEING EMPTIED.**

**OTHER PRECAUTIONS:** Avoid breathing vapors. Avoid prolonged or repeated contact with skin. Remove contaminated clothing; wash before re-use. Wash skin with soap and water after contact.

**SECTION VIII - EXPOSURE CONTROLS AND PERSONAL PROTECTION:**

	OSHA				ACGIH	
	TWA		STEL		TWA	
	PPM	MgM3	PPM	MgM3	PPM	MgM3
	400	980	500	1225	400	980
Carcinogen - NTP Program .....	N/A					
Carcinogen - IARC Program .....	N/A					

**EFFECTS OF OVEREXPOSURE:** Avoid breathing vapor. Inhalation of high vapor concentrations may have results ranging from dizziness and headaches to unconsciousness. Prolonged or repeated liquid contact will dry and defat the skin leading to irritation and dermatitis.

**RESPIRATORY PROTECTION (Specify type).** Hydrocarbon vapor canister or supplied-air hose made if needed.

**VENTILATION:**

- LOCAL EXHAUST ..... Face velocity > 60 fpm
- MECHANICAL (General) ..... Explosion - proof ventilation equipment.
- SPECIAL ..... Use only with adequate\* ventilation
- OTHER ..... No smoking or open flames.

**PROTECTIVE GLOVES:** Normally not needed. Use chemical resistant gloves if necessary.

**EYE PROTECTION:** Normally not needed.

**OTHER PROTECTION EQUIPMENT.** Hydrocarbon insoluble apron if needed.

**SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES.**

BOILING POINT .....	176°F
VAPOR PRESSURE (mmHG).....	32 @ 68°F
VAPOR DENSITY (AIR =1).....	2.1
SOLUBILITY IN WATER .....	partial
SPECIFIC GRAVITY (H2O =1) .	0.82
PERCENT, VOLATILE BY VOLUME (%) .....	100
VAPORATION RATE .....	1.4
APPEARANCE .....	yellow
ODOR .....	solvent

**PAGE 4**

**SECTION X - STABILITY AND REACTIVITY:**

STABILITY .....	Stable
INCOMPATIBILITY (Materials to avoid) .....	NONE
HAZARDOUS DECOMPOSITION PRODUCTS .....	Will not occur
HAZARDOUS POLYMERIZATION .....	Will not occur

**CONDITIONS TO AVOID:**

1. Prolonged or repeated breathing of vapors
2. Contact with eyes
3. Prolonged or repeated contact with skin

**SECTION XI - TOXICOLOGICAL INFORMATION**

This product does not contain any toxic chemicals that are subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

**SECTION XII - ECOLOGICAL INFORMATION**

**THIS PRODUCT DOES NOT CONTAIN ANY OZONE DEPLETING CHEMICALS**

**SECTION XIII - DISPOSAL CONSIDERATIONS**

**WASTE DISPOSAL:** This product, if discarded, becomes a hazardous waste under CERCLA. Use the following information:

Proper Shipping Name: **RQ Waste Flammable Liquid N.O.S.**  
Class: **3**  
I.D. Number: **UN 1993**  
Pk Group: **II**  
RCRA WASTE Number: **D001**

Waste disposal should be in compliance with federal, state and local law.

**SECTION XIV - TRANSPORTATION INFORMATION**

PART #1105 (pails) and Part #1155 (drums)  
**PROPER SHIPPING NAME: FLAMMABLE LIQUID, NOS (HYDROXY COMPOUNDS)**  
**HAZARD CLASS: 3**  
**I.D NUMBER UN 1993**  
**PACKING GROUP: II**  
**PLACARDING: REQUIRED WHEN WEIGHT IS OVER 1000 POUNDS**

**PAGE 5**

PART #1025 - 32oz (Case), #1041 - 96oz (Case)

PROPER SHIPPING NAME: **FLAMMABLE LIQUID, NOS (HYDROXY COMPOUNDS)**

HAZARD CLASS: **3**

ID NUMBER: **UN 1993 "LIMITED QUANTITY"**

PACKING GROUP: **3**

PLACARDING: **NOT REQUIRED**

SPECIAL PACKING: **NOT REQUIRED**

**SECTION XV - REGULATORY INFORMATION**

RIGHT TO KNOW TIER II REPORTING INFORMATION: **SECTION 311-312**

CHEMICAL DESCRIPTION: **HYDROXY COMPOUNDS AND HYDROCARBONS**

COMMON (LABEL) NAME: **DIESEL FUEL SUPPLEMENT**

TYPE OF PRODUCT: **MIX - LIQUID**

PHYSICAL HAZARD - **FIRE**

HEALTH HAZARD - **IMMEDIATE (ACUTE)**

REACTIVITY: **NONE**

EXTREMELY HAZARDOUS SUBSTANCES: **NONE**

EMERGENCY RESPONSE GUIDE BOOK PAGE NUMBER: **26**

NFPA RATING:

HEALTH: **2**

FIRE: **3**

REACTIVITY: **0**